



® Knowledge Beyond Measure.

Q-Trak™ XP Indoor Air Quality Monitor

Model 7585



The Q-Trak™ XP Indoor Air Quality Monitor Model 7585 combines multiple gas and particle measurements into a single lightweight, handheld instrument that is easy to use, configure and calibrate in the field.

Designed for IAQ and industrial hygiene professionals, the Q-Trak XP™ Indoor Air Quality Monitor can perform a wide range of indoor air quality assessments. The powerful, compact multi-sensor module is equipped to measure up to 20 IAQ parameters. Export data in a single file for easy graphing and analysis.

The Q-Trak™ XP Indoor Air Quality Monitor Model 7585 combines multiple gas and particle measurements into a single lightweight, handheld instrument that is easy to use, configure and calibrate in the field. Designed for IAQ and industrial hygiene professionals, the Q-Trak™ XP Indoor Air Quality Monitor can perform a wide range of indoor air quality assessments. The powerful, compact multi-sensor module is equipped to measure up to 20 IAQ parameters. Export data in a single file for easy graphing and analysis.

Features and Benefits

- Simultaneously measures and logs up to 20 IAQ parameters, including mass concentration and gas — in one instrument
- Measures PM1, PM2.5, PM10 size fractions and particle concentration
- Accommodates up to 6 optional, pre-calibrated gas sensors
- Built-in % of outdoor air workflow
- Field calibration and replacement of sensors, minimizing downtime
- Monitor temperature and relative humidity with wet bulb and dew point calculations
- Real-time temperature and barometric pressure density compensation for TVOC and CO₂
- Large touch-screen with intuitive navigation
- Export data remotely with Wi-Fi connectivity

Ideal For

- Commercial and office buildings
- Schools and universities
- Hospitals and healthcare facilities
- Public buildings and shopping centers
- Transportation hubs (airports, bus and train depots)

Q-TRAK XP INDOOR AIR QUALITY IAQ MONITOR 7585

TrakPro™ Ultra Software

The Q-Trak™ XP Indoor Air Quality Monitor includes the new TrakPro™ Ultra software. From the dashboard of this new software, users can connect directly to the instrument, to download and graph data for analysis.

Data Collection and Reporting

Expanded data logging capacity of the Q-Trak™ XP Indoor Air Quality Monitor coupled with the included TrakPro™ Data Analysis Software provides the capabilities to work effectively and efficiently as you move from data collection to report generation.

The Q-Trak XP Indoor Air Quality Monitor can store over 100 days of data collected at one-minute log intervals. TrakPro Ultra allows for seamless transfer to your PC, so stored data can be recalled, reviewed on screen, and downloaded for data analysis, graphing and exporting for building reports. This software is useful for analyzing long term, unattended data logging studies common in IAQ investigations.

Wi-Fi wireless connection connects the TrakPro Ultra software on your PC directly to the Q-Trak XP Indoor Air Quality Monitor or via a local network to capture and download data remotely.

- Simple and fast data transfer / download from Q-Trak XP Indoor Air Quality Monitor to PC
- Review and graph multiple parameters to investigate trends
- User-define graph parameters for data analysis
- Review data charts of defined parameters
- Graph creation for generating reports
- Instrument programming



Q-TRAK XP INDOOR AIR QUALITY IAQ MONITOR 7585

Gas Sensor Options

The Q-Trak™ XP Indoor Air Quality Monitor Model 7585 can be configured to monitor a variety of gases. A total of 6 sensors can be installed and used at one time, with the ability to mix-and-match. Please note, the Model 7585 kit includes one carbon dioxide sensor.

All sensors are pre-calibrated and include a certificate of calibration.



| Carbon Dioxide Sensor (CO ₂) - 801399 | |
|---|-------------------------------|
| Sensor Type | NDIR (Nondispersive Infrared) |
| Range | 0 - 5000 ppm |
| Accuracy ¹ | ± 50 ppm |
| Resolution | 1 ppm |
| Response Time (t90) | < 40s @ 20°C ambient |

| TVOC Sensor (ppb) - 801408 | |
|----------------------------|---------------------------------|
| Sensor Type | PID (Photo Ionization Detector) |
| Range | 0 - 20,000 ppb |
| Resolution | 10 ppb |
| Response Time (t90) | <3 seconds |

| Formaldehyde Sensor (H ₂ CO) - 801409 | |
|--|-----------------|
| Sensor Type | Electrochemical |
| Range | 0-10 ppm |
| Accuracy | ± 0.3 ppm |
| Resolution | 0.01 ppm |
| Response Time (t90) | < 90 seconds |

| Chlorine Sensor (CL ₂) - 801400 | |
|---|---------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-20 ppm |
| Accuracy | ± 0.3 ppm |
| Resolution | 0.01 ppm |
| Response Time (t90) | < 60 seconds from zero to 10ppm |

| Nitrogen Dioxide Sensor (NO ₂) - 801405 | |
|---|--------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-20 ppm |
| Accuracy | ± 0.5 ppm |
| Resolution | 0.01 ppm |
| Response Time (t90) | < 80 seconds from zero to 2ppm |

| Hydrogen Sulfide Sensor (H ₂ S) - 801402 | |
|---|--------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-50 ppm |
| Accuracy | ± 0.5 ppm |
| Resolution | 0.01 ppm |
| Response Time (t90) | < 60 seconds from zero to 2ppm |

| Carbon Monoxide Sensor (CO) - 801401 | |
|--------------------------------------|---------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-400 ppm |
| Accuracy | ± 2% of reading ± 1 ppm |
| Resolution | 0.1 ppm |
| Response Time (t90) | < 30 seconds from zero to 10ppm |

| TVOC Sensor (ppm) - 801407 | |
|----------------------------|---------------------------------|
| Sensor Type | PID (Photo Ionization Detector) |
| Range | 0-2000 ppm |
| Resolution | 0.1 ppm |
| Response Time (t90) | <3 seconds |

| Ozone Sensor (O ³) - 801406 | |
|---|--------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-20 ppm |
| Accuracy | ± 0.3 ppm |
| Resolution | 0.01 ppm |
| Response Time (t90) | < 80 seconds from zero to 1ppm |

| Ammonia Sensor (NH ³) - 801403 | |
|--|-----------------|
| Sensor Type | Electrochemical |
| Range | 0-100 |
| Accuracy | ± 1 ppm |
| Resolution | 0.1 ppm |
| Response Time (t90) | < 45 seconds |

| Nitric Oxide Sensor (NO) - 801404 | |
|-----------------------------------|--------------------------------|
| Sensor Type | Electrochemical |
| Range | 0-20 ppm |
| Accuracy | ± 0.2 ppm |
| Resolution | 0.1 ppm |
| Response Time (t90) | < 25 seconds from zero to 2ppm |

t90: Time to achieve 90% of the actual concentration
¹ CO₂ accuracy based on density correction activated



Inside the multi-sensor tray

Specifications

Q-Trak™ XP Indoor Air Quality Monitor Model 7585

The Q-Trak™ XP Indoor Air Quality Monitor Model 7585 arrives from the factory with the following preset technical specifications.

Particles

| | |
|-----------------------|---|
| Sensor Type | Optical Particle Counter (OPC) |
| Particulate Mass (PM) | PM1.0, PM2.5, PM10 |
| Range | 0 to 500 µg/m ³ |
| Accuracy | ±10 µg/m ³ (0 - 100 µg/m ³), ±10% of reading 100 - 500 µg/m ³ |
| PM Resolution | 1 µg/m ³ , 0.001 mg/m ³ |
| PM Units | µg/m ³ , mg/m ³ |

Particle Concentration

| | |
|----------------------------|--|
| (PC sizes in microns (µm)) | PC0.3, PC0.5, PC1.0, PC2.5, PC5.0, PC10.0 |
| PC Resolution | 0.01/cm ³ , 1/ft ³ , 1/L |
| PC Units | #/cm ³ , #/ft ³ , #/L |
| Response Time | <10 seconds |

Carbon Dioxide

| | |
|---------------------|-------------------------------|
| Sensor Type | Nondispersive Infrared (NDIR) |
| Range | 0 - 5000 ppm |
| Accuracy | ± 50 ppm |
| Resolution | 1 ppm |
| Response Time (t90) | < 40s @ 20° C ambient |

Temperature

| | |
|---------------------|------------------------------------|
| Range | 32 - 140°F (0 - 60° C) |
| Accuracy | ± 1.0°F (0.5° C) |
| Resolution | 0.1°F (0.1° C) |
| Response Time (t90) | < 15 seconds to 90% of final value |

This instrument is not designed for confined spaces in which respirators may be required, or in hazardous and/or explosive environments.

Specifications are subject to change without notice.

TSI, and the TSI logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.

Relative Humidity

| | |
|---------------------|---------------------------------|
| Sensor Type | Capacitance |
| Range | 0 - 100% RH |
| Accuracy | ± 3% RH |
| Resolution | 0.1 % RH |
| Response Time (t63) | 8 Seconds to 63% of final value |

Barometric Pressure

| | |
|---------------------|--|
| Range | 7.7 - 37.2 in Hg (196.0 - 945.0 mm Hg) |
| Accuracy | ±0.12 in Hg (±3.0 mm Hg) |
| Resolution | 0.01 in Hg (0.1 mm Hg) |
| Response Time (t63) | >2 seconds to 63% of final value |

Operating Parameters

| | |
|-----------------------|--|
| Logging Capability | 73,000,000 data points |
| Operating Temperature | 41 - 104° F (5 - 40° C) |
| Storage Temperature | -4 - 140° F (-20 - 60° C) |
| Meter Dimensions | 3.8 in. × 8.3 in. × 2.1 in. (9.7 cm × 21.1 cm × 5.3 cm) |
| Weight with Batteries | 1.2 lbs./0.55 kg |
| Power Requirements | Li-ion rechargeable battery pack or universal AC adapter - both included |
| Languages Supported | English, German, French |

The Q-Trak™ XP Indoor Air Quality Monitor Model 7585 kit includes:

Handheld unit with multi-sensor IAQ module (includes sensors for temperature, relative humidity, barometric pressure, particle mass concentration, plus open slots for six different types of gases)

- Co₂ Gas Sensor
- Carrying Case
- Communication Cable
- Power Supply
- Calibration Certificate
- Gas Calibration Cap
- Trakpro Ultra Software (Download)
- Li-Ion Battery Pack
- Manual

Optional Accessories

| Specify | Description |
|---------|---|
| 801430 | Multi-Sensor IAQ Module with PM 2.5, Temperature, Relative Humidity, Barometric Pressure, and 6 Open Sensor Slots for Expansion |
| 800125 | Battery Cover with Tripod Mount |
| 800128 | Q-Trak XP Tabletop Tripod |
| 800129 | Q-Trak XP Battery Cover with Tripod Mount and Tabletop Tripod |
| 800124 | Wi-Fi Dongle |