

Benchtop Rapid Extractor – FT110DP

The Armfield FT110DP Benchtop Rapid Extractor is used to extract the active constituents from small (<1 litre) samples of materials.

This single piston pressure system gives rapid results from small volumes while giving flexibility to the operator with the processing parameters.

The three phases of operation are pressurisation, relaxation and dynamic percolation. This forces the solution into the biomass, dissolves the active ingredient and recovers the solution into a separate vessel.

**FAST RESPONSE, RESULTS IN HOURS
DATA LOGGING
DUAL PUMP**



Features / benefits

- ▶ Fast response, results in hours rather than days
- ▶ Small scale, only one litre of raw material is required
- ▶ Simple cleaning and maintenance procedures
- ▶ Uses ethanol, glycerol, water or similar safe polar solvents
- ▶ Reproducible results
- ▶ Fast, efficient solid/liquid extraction of active constituents from plants, herbs, fruits and other similar materials
- ▶ Computer Controlled
- ▶ Data Logging
- ▶ Accurate scale up
- ▶ Includes one process vessel, two solvent vessels
- ▶ Remote Control via VPN
- ▶ Touch Screen Membrane Control Panel
- ▶ High pressure, room temperature extraction, excellent for sensitive material
- ▶ Unaltered natural properties and characteristics of the active constituents, no discolouration or oxidation
- ▶ Easy to use: microprocessor control and real time display of sequencing and process parameters
- ▶ Automatic pressure control
- ▶ Automatic alarm indication of process anomalies
- ▶ Highly flexible extraction parameters

UK office - email: sales@armfield.co.uk tel: +44 (0) 1425 478781 (for ROW)
USA office - email: info@armfield.inc tel: +1 (609) 208-2800 (USA only)

Issue: 2

URL: <http://www.armfield.co.uk/ft110>

We reserve the right to amend these specifications without prior notice. E&OE © 2019 Armfield Ltd. All Rights Reserved

Description

The Armfield FT110DP uses high pressure and a combination of both static and dynamic extraction phases to achieve a rapid extraction of the active materials with minimum degradation to the product. In the dynamic phases, the solvent is passed through the material providing a forced percolation and agitation.

The process pressure, number of cycles and length of each phase are programmable by the user. In this way the effect of the extraction parameters on the end product can be explored and an optimum set of parameters determined for each product.

The FT110DP vessel is loaded with solvent and primed manually. A single pneumatic piston is used to generate the pressure in the vessel and to provide the solvent percolation using a novel system of valves.

Included are two 5 litre external vessels. One for recirculation and solvent storage and one for solvent recovery.


Applications

- ▶ Natural Food Flavours
- ▶ Fruit Flavours
- ▶ Herbs and Plant extracts
- ▶ Spirit liquors
- ▶ Tinctures and infusions
- ▶ Herbal extracts and homeopathy
- ▶ Cosmetics
- ▶ Pharmaceuticals

Technical specifications

Process vessel volume options	0.5L, 1L, 2L
Total solvent capacity	5L
Maximum pressure	8 bar
External Vessel Capacity	5L each (two supplied as standard)
Number of Pistons	2 Pistons

High pressure extraction



Requirements

Scale



- ▶ **Electrical supply:** Single phase (see ordering codes)
- ▶ **Compressed Air (or N₂)** 8 bar

Overall dimensions

Length	0.70m
Width	0.35m
Height	0.55m

Packed and crated shipping specifications

Volume	0.3m ³
Gross weight	40Kg



FT110DP Twin pistons



FT110DP Process vessel

Ordering codes

- ▶ **FT110DP-A** 220-240V/1ph/50Hz, 0.5 kW
- ▶ **FT110DP-B** 115V/1ph/60Hz, 0.5 kW
- ▶ **FT110DP-G** 220-240V/1ph/60Hz, 0.5 kW

Armfield standard warranty applies with this product

Knowledge base

- > 28 years expertise in research & development technology
- > 50 years providing engaging engineering teaching equipment

Benefit from our experience, just call or email to discuss your laboratory needs, latest project or application.

An ISO 9001:2015 Company



armfield.co.uk

Aftercare

Installation
Commissioning
Training
Service and maintenance
Support: armfieldassist.com